




WORKING DIAGRAM



INFO

-  **OUTRIGGERS**
H+H
-  **WORKING HEIGHT**
13,50 m
-  **BASKET HEIGHT**
11,50 m
-  **MAX OUTREACH**
7,10 m
-  **BASKET LOAD CAPACITY**
230 kg
-  **BASKET SIZE**
1200x700x1100 mm
-  **BASKET ROTATION**
90° + 90°
-  **CONTROLS**
Electric
-  **TURRET ROTATION**
700°
-  **GVW**
3,19 ton


STANDARD ACCESSORIES

- Cables and hoses installed inside the boom
- Proportional electrohydraulic controls with regulation of the speed of all movements
- Electronic safe system CAN BUS
- 4 outrigger plates
- Socket 230V and 12V in the basket
- Possibility of simultaneous movements
- Automatic regulation of engine revolutions
- Cataphoresis treatment with powder coating
- Aerial part centering light on the basket

SAFETY DATA

- **Socage Security System**
- Unintentional maneuver protection bar
- Controls protection of the basket
- Circuit breaker with differential protection on the 230V line
- Safety bypass for operator rescue
- Moment limiting device with double security
- Self levelling system for the basket
- Indinometer
- Flanged block valves
- Emergency button
- Emergency manual hand pump
- Possibility emergency remote rescue
- Automatic PTO deactivation
- Smart anti crash cab protection
- Electrical hour counter
- Cab light closed outriggers
- Maintenance light (service)

MINIMUM AREA



MAXIMUM AREA